



30 m
max. range
of spray

FOG CANNON HE30F

The HE30F cannon comes as a „turn key“ solution complete with an in-built generator. It is a perfect unit for smaller job sites lacking a convenient power source.

APPLICATIONS & INDUSTRIES

Demolition & Construction
Coal handling & Power generation
Mining & Quarrying
Bulk materials ports & Shipping
Steel & Slag
Waste Transfer
Recycling & Scrap
Wood Processing

SPECIAL APPLICATIONS

Watering and chemical spraying (golf courses, agriculture, mosquito areas etc.)
Dispersing of disinfectant for sanitizing of indoor and outdoor spaces

BASIC MODEL INCLUDES:

Rear mounted axial fan
High-efficiency spray nozzles
Central column support to enable horizontal rotation
Booster pump
Water filter, pressure gauge
Electric control panel
Road trailer with water bowser system and in-built generator

TECHNICAL SPECIFICATION	HE30F
Throw (meters)	up to 30 (still conditions)
Coverage (m ²)	approx. 1415
Droplet size (µm)	50-150
Booster pump (kW)	1,5
Fan (kW)	4,0
Horizontal rotation	0-180°
Adjustable vertical elevation	0-40°
Water consumption (l/h)	1000
Nozzles quantity (pcs)	18
Power supply (diesel engine)	15 kW, 3 x 400 V AC, 50 Hz
Run time (hours)	approx. 10
Water bowser (l)	2000

